Skill S	heet No. FF-I- 801 07	7-01-07 Candidate Number				
Skill T	Title: SELECTION AND USE OF I	PORTABLE EXTINGUISHERS	,			
NFPA	Objective: 5.3.16	Minimum to pass	10			
PERF	ORMANCE:	*	Р	F		
<u> </u>						
1.	Wears full protective clothing and utilize	s positive pressure SCBA.				
2.	Selects correct extinguisher given the size	e of the fire and the type of fuel				
	burning.					
	Ordinary Combustibles					
	Flammable Liquids					
	Flammable Gases					
	Energized Electrical Equipment					
3.	Carries extinguisher to a safe distance from fire.					
4.	Pulls pin at top of extinguisher, if equipped, and breaks seal.					
5.	Stands to the side of the extinguisher and charges by activating the					
	cartridge, if equipped.					
6.	Tests extinguisher to assure proper agent					
7.	Shuts off electricity to the burning object					
8.	Approaches fire from the upwind and up					
9.	Begins discharging agent from a safe dist	ance.				
10.	Properly discharges the extinguishing age	ent based on the fire and fuel				
	burning.					
11.	Keeps carbon dioxide extinguisher on the	e ground while discharging agent, if				
	applicable.					
12.	Sweeps the extinguisher nozzle while disc	charging agent.				
13.	Assures that the fire is extinguished.					
14.	On class B or B/C backs away from the fo	uel source after fire is extinguished.				

Failure of this critical portion is cause for entire skill failure						
Examiner Name						
Examiner Signature	Date/					

S	kill Sl	heet No. FF-I- 802 07-01-07 Candidate Number				
S	kill T	itle: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS FIR	E-NOZ	ZLE		
		FIREFIGHTER				
N	FΡΔ	Objective: 5.3.10 Minimum to pass	15			
_		DRMANCE:	P	F		
Γ.	CKTC	JRIVIANCE.	Г	Г		
	1.	Wears full protective clothing and utilizes positive pressure SCBA.				
	2.	Activates PASS device.				
	3.	Sets nozzle for a 30-degree fog pattern with a minimum flow of 95 GPM.				
	4.	Slowly opens the nozzle fully, prior to entering the structure, to expel air				
		and test the fog pattern.	_	_		
	5.	Feels door low to high, using the back of an ungloved or partially ungloved				
		hand, prior to opening.				
	6.	Assures that the other two firefighters are ready to enter the structure.				
	7.	Stays low when entering structure displaying hostile/low visibility				
		conditions.				
	8.	Advances hoseline to fire room while approaching from the unburned side.				
	9.	Keeps nozzle closed while advancing to fire unless necessary to operate for				
		protection.				
	10.	Upon reaching fire, manages fire stream safely and properly based on the				
		conditions present.				
	11.	Calls for first backup firefighter to ventilate structure, calls for second				
		backup to start overhaul.				
	12.	Places nozzle outside of the building opening in preparation for hydraulic				
		ventilation.				
	13.	Slowly opens the nozzle.				
	14.	Retracts the nozzle into the building approximately two (2) feet.				
	15.	Adjusts fog pattern to fill approximately the upper 85-90% of the opening				
		with the stream slightly touching the sides of the opening.				
	16.	Holds stream steady until smoke has cleared or else is ordered back to the				
		fire origin.				
	17.	Stops hydraulic ventilation by advancing the nozzle outside the building				
	4.6	opening.				
	18.	Slowly closes the nozzle.				
	19.	Assures fire is overhauled and extinguished.				
	20.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause	for entire skill failure
Examiner Name	
Examiner Signature	Date/

Firefighter Fractical Certification Examination							
Skill Sheet No. F	F-I- 803	07-01-07	Candidate Number	er			
Skill Title: EXTI	Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS FIRE						
FIRST BACKUP							
NFPA Objective: 5.3.10 & 5.3.11 Minimum to pass					11		
PERFORMANCE:					P		F
1. Wears full pr	otective clothing and ut	ilizes positive	pressure SCBA.				
2. Activates PASS device.							
3. Takes a position on the same side of the hoseline relative to nozzleman.							
4. Carries a fore	Carries a forcible entry tool.						
5. Stays low who	Stays low when entering structure displaying hostile/low visibility						
70.0						_	

3.	Takes a position on the same side of the nosemie relative to nozzieman.		
4.	Carries a forcible entry tool.		
5.	Stays low when entering structure displaying hostile/low visibility conditions		
6.	Remains behind nozzleman far enough to advance hose to him/her.		
7.	Removes kinks in hoseline during advancement.		
8.	Keeps hoseline opposite protruding corners to avoid kinking.		
9.	Advances hoseline based on the need of the nozzle firefighter.		
10.	Joins the nozzle firefighter after the hoseline is in position.		
11.	Upon order from nozzle firefighter ventilates structure.		
12.	Assists with overhaul of burning materials with a tool, not the hands.		
13.	Orders nozzle firefighter back to origin to wet burning materials if necessary.		
14.	Assures fire is overhauled and extinguished.		
15.	Completes evolution using safe fire suppression skills.		

Failure of this critical portion is cause for entire skill failure						
Examiner Name						
Examiner Signature	Date/					

Skill S	Sheet No. FF-I- 804 07-01-07 Candidate Number				r				
Skill T	itle: EX	KTINGUISH AN INTEF	RIOR CLAS	S "A" MATERIALS	S FIRE	SEC	COI	ND	
	BA	ACKUP							
NFPA	Objective:	5.3.10 & 5.3.13		Minimum to pass		9			
PERFO	ORMANCI	E:		<u> </u>		P		F	
	T								
1.	Wears full protective clothing and utilizes positive pressure SCBA.								
2.	Activates 1	PASS device.							
3.	Takes a po	osition on the same side of	the hoseline r	elative to nozzleman.					
4.		orcible entry tool.			ſ				
5.		when entering structure d	isplaying host	tile/low visibility					
	conditions	;.							
6.	Remains o	outside of doorways while a	advancing hos	seline.					
7.		kinks in hoseline during ad							
8.		seline opposite protruding							
9.	Advances	hoseline based on the need	d of the nozzle	e firefighter.					
10.		back away from the first ba	ackup firefigh	iter in preparation to					
	advance m	nore hose.							
11.	Moves up	to fire area if called by the	e nozzle, the fi	irst backup firefighter,	, or				
	once extra	hose is no longer needed.							
12.	Overhauls	s burning materials when o	ordered by no	zzle firefighter.	Ī				
13.	Completes	s evolution using safe fire s	suppression sl	xills.					

Failure of this critical portion is cause	for entire skill failure
Examiner Name	
Examiner Signature	

Skill S	heet No.	FF-I- 8	05	07-01-0)7	Candidate Number	er				
Skill T	itle: EX	TINGU	ISH A VEHIC	CLE FIRE-I	VOZ	ZZLE FIREFIGHT	ER				
NFPA	Objective:	5.3	.7		N.	Iinimum to pass		1	1		
PERFO	ORMANCI	Ξ:]	P		F
1.						pressure SCBA.					
2.	Sets nozzle for a straight stream pattern with a minimum flow of 95 GPM.					PM.					
3.	Slowly ope	ens the no	zzle fully, prio	r to approac	ning	vehicle, to expel air	and				
	test the str			• •	Ü	•		_		_	
4.	Assures ot	her two f	irefighters are	ready to app	roac	ch.					
5.	Advances	from uph	ill, upwind, and	d from the si	de o	f the vehicle if possik	ole.				
6.	Advances	closed ho	seline to appro	ximately 100	feet	from vehicle.					
7.	Slowly opens the nozzle.										
8.	Properly and safely manages fire stream to cool vehicle hazard area. (Fuel				uel						
	tanks, eng	ine comp	artment throug	h radiator, t	ires,	split rims, bumpers	, air				
	suspension	systems,	, drive shafts, e	tc.)							
9.	Extinguish	es surrou	unding fires, if	present.							
10.	Cools expo	sures, if	present.								
11.	Increases i	fog patter	n size as distan	ce to vehicle	is r	educed.					
12.	Orders fir	st backup	firefighter to	open vehicle	com	partments. (Door, h	ood,				
	and trunk)									
13.	Extinguish	es fire as	exposed.								
14.	Assures fin	e is overl	hauled and exti	nguished.							

Failure of this critical portion is cause for entire skill failure						
Examiner Name						
Examiner Signature	_ Date/					

Skill S	Skill Sheet No. FF-I- 806 07-01-07 Candidate Number						
Skill T	itle: EXTINGUISH A	VEHICLE FIRE-FIRST BACKUP					
NFPA	Objective: 5.3.7	Minimum to pass	3	7			
PERFO	DRMANCE:			P		F	
1.	Wears full protective cloth	ing and utilizes positive pressure SCBA.					
2.	. Takes a position on the same side of the hoseline relative to nozzleman.						
3.	Carries a forcible entry to	ol.					
4.	Advances hoseline based o	n the need of the nozzle firefighter.					
5.	Removes kinks in hoseline	during advancement.					
6.	Joins the nozzle firefighter once the hoseline is in position.						
7.	Upon order from nozzle firefighter, opens vehicle compartments. (Doors,						
	hood, and trunk)						
8.	Overhauls burning materi	als with the tool.					
9.	Orders nozzle firefighter b	ack to wet burning materials, if necessary	y•				
10.	Assures fire is overhauled	and extinguished.					

Failure of this critical portion is cause	for entire skill failure	
Examiner Name	-	
Examiner Signature	_ Date/	

Skill Sheet No. FF-I- 807 07-01-07 Candidate Number									
S	Skill Title: EXTINGUISH A VEHICLE FIRE-SECOND BACKUP								
N	NFPA Objective: 5.3.7 Minimum to pass								
P	PERFORMANCE:							F	
	1.	Wears full protective clothing and utiliz	es positive press	sure SCBA.					
	2.	Takes a position on the same side of the	hoseline relativ	e to nozzleman.					
	3.	Advances hoseline based on the need of	the first backup	firefighter.					
	4.	Removes kinks in hoseline during adva-	ncement.						
	5.	Remains back away from the first back	up firefighter in	preparation to					
		advance more hose.	•	• •					
	6.	Moves up to origin if called by the nozz	e, first backup f	firefighter, or once					
		the need for more hose ceases.	_						
	7.	If safe, properly disconnects battery fro	m vehicle. (Neg	ative side first.)					
	8.	Assists first backup firefighter with ope	ning vehicle con	npartments. (Doors	,				
		Hood and trunk)							
	9.	Assists with overhauling burning mater	ials.						
	10.	Assures fire is overhauled and extinguis	hed.						

Failure of this critical portion is cause	e for entire skill failure
Examiner Name	_
Examiner Signature	Date/

Skill Sheet No. FF-I- 808 07-01-07 Candidate Number													
Skill Title: EXTINGUISH A DUMPSTER FIRE-NOZZLE FIREFIGHTER													
N	NFPA Objective: 5.3.8 Minimum to pass									11			
P	PERFORMANCE:									P		F	
	1.							pressure SCBA.					
	2.	Sets nozzlo	e for	a straight str	eam patt	tern with a	miı	nimum flow of 95 G	PM.				
	3.	Slowly ope	ens tl	he nozzle full	y, prior t	o approacl	hing	dumpster, to expel	air	_			
		and test th	e str	eam pattern.									
	4.	Assures th	at th	ne other two f	irefighte	rs are read	ly to	approach.					
	5.	Advances	fron	n uphill and u	pwind, if	f possible.							
	6.	Advances closed hoseline to approximately 100 feet from dumpster.											
	7.	Slowly ope	ens tl	he nozzle.									
	8.				es fire str	eam to coo	l th	e dumpster and					
		surroundi	_										
	9.			urrounding f									
	10.	Orders fir	st ba	ckup firefigh	ter to op	en dumpst	er o	penings. (Top or si	des)				
	11.			re as exposed									
	12.	Hydraulic	ally	overhauls ma	terial as	much as p	ossi	ble limiting personn	el				
		exposure.											
	13.	Does not u	se ex	xcessive press	sure duri	ng overhau	ıl to	avoid blowing and					
				terial on pers									
	14.	Assures fin	re is	overhauled a	nd exting	guished.							

Failure of this critical portion is cause f	for entire skill failure
Examiner Name	
Examiner Signature	Date/

Skill Sheet No. FF-I- 809 07-01-07 Candidate Number									
S	Skill Title: EXTINGUISH A DUMPSTER FIRE-FIRST BACKUP								
NFPA Objective: 5.3.8 Minimum to pass									
P	PERFORMANCE:						F		
	1.	Wears full protective clothing and uti	ilizes positive pressure SCBA.						
	2.	Takes a position on the same side of t	he hoseline relative to nozzleman.						
	3.	Carries a forcible entry tool.							
	4.	Advances hoseline based on the need	of the nozzle firefighter.						
	5.	Removes kinks in hoseline during adv							
	6.	Joins the nozzle firefighter once the h	oseline is in position.						
	7.	Upon order from nozzle firefighter, o	pens dumpster openings with a tool.						
		(Top or side)							
	8.	• •	overhauls burning material with tool,						
		if necessary, limiting exposure to pers	sonnel.						
	9.	Orders nozzle firefighter back to wet	burning materials.						
	10.	Assures fire is overhauled and extingu	uished.						

Failure of this critical portion is cause for entire skill failure										
Examiner Name	_									
Examiner Signature	Date/									

Skill Sheet No. FF-I- 810 07-01-07 Candidate Number											
Sl	kill Ti	itle: EX	TIN	NGUISH A DUM	PSTER FIR	E-S	ECOND BACKU	P			
N	NFPA Objective: 5.3.8 Minimum to pass									7	
PI	PERFORMANCE:									P	F
	1.	Wears full protective clothing and utilizes positive pressure SCBA.									
	2.	Carries a	forci	ible tool							
	3.	Takes a po	sitio	on on the same side	of the hoseling	ne re	elative to nozzleman.				
	4.	Advances	hose	eline based on the n	eed of the firs	st ba	ckup firefighter.				
	5.	Removes l	kinks	s in hoseline during	g advancemen	ıt.					
	6.	Remains b	ack	away from the firs	t backup fire	fight	ter in preparation to				
		advance m	ore	hose.							
	7.	Moves up	to or	rigin if called by the	e nozzleman,	first	backup firefighter,	or			
		once the n	eed f	for more hose cease	es.						
	8.	Assists firs	st ba	ckup firefighter wi	th opening d	ımp	ster openings with to	ool.			
		(Top or sid	des)								
	9.	Hydraulic	ovei	rhaul is preferred,	but overhauls	s bu	rning material with	tool,			
		if necessar	y, liı	miting exposure to	personnel.						
	10.	Assures th	at o	verhaul is complete	and fire is ex	kting	guished.				

Failure of this critical portion is cause	for entire skill failure	
Examiner Name	-	
Examiner Signature	_ Date/	

~ 1												
Skill Sheet No. FF-I- 811 07-01-07 Candidate Number												
S	Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS ABOVE											
	GRADE FIRE - NOZZLE FIREFIGHTER											
NFPA Objective: 5.3.10 Minimum to pass												
_		DRMANCE:	15 P	F								
1		d Oldvir hace.										
	1.	Wears full protective clothing and utilizes positive pressure SCBA.										
	2.	Activates PASS device.										
	3.	Sets nozzle for a 30-degree fog pattern with a minimum flow of 95 GPM.										
	4.	Slowly opens the nozzle fully, prior to entering the structure, to expel air										
		and test the fog pattern.										
	5.	Feels door low to high, using the back of an ungloved or partially ungloved										
		hand, prior to opening.										
	6.	Assures that the other two firefighters are ready to enter the structure.										
_	7.	Stays low when entering structure displaying hostile/low visibility										
		conditions.										
	8.	Advances hoseline to fire room while approaching from the unburned side.										
	9.	Avoids staying in stairwells.										
	10.	Keeps nozzle closed while advancing to fire unless necessary to operate for										
		protection.										
	11.	Upon reaching fire, manages fire stream safely and properly based on the										
		conditions present.										
_	12.	Calls for first backup firefighter to ventilate structure, calls for second		_								
		backup to start overhaul.										
	13.	Places nozzle outside of the building opening in preparation for hydraulic										
	4.4	ventilation.										
	14.	Slowly opens the nozzle.										
	15.	Retracts the nozzle into the building approximately two (2) feet.										
	16.	Adjusts fog pattern to fill approximately the upper 85-90% of the opening										
	15	with the stream slightly touching the sides of the opening.										
	17.	Holds stream steady until smoke has cleared or else is ordered back to the										
	10	fire origin.										
	18.	Stops hydraulic ventilation by advancing the nozzle outside the building										
	10	opening.										
	19.	Slowly closes the nozzle.										
	20.	Assures fire is overhauled and extinguished.										
	21.	Completes evolution using safe fire suppression skills.										

Failure of this critical portion is cause f	for entire skill failure
Examiner Name	
Examiner Signature	Date/

Skill Sheet No. FF-I- 812 07-01-07 Candidate Number										
S	Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS ABOVE									
	GRADE FIRE - FIRST BACKUP									
NFPA Objective: 5.3.10 & 5.3.11 Minimum to pass								11		
_	PERFORMANCE:									F
	1.		l protective clothing a	nd utilizes posi	tive	pressure SCBA.				
	2.	Activates 1	PASS device.							
	3.		osition on the same sid	de of the hoselii	ne re	lative to nozzleman.				
	4.		forcible entry tool.							
	5.		when entering structu	ıre displaying l	osti	le/low visibility				
		conditions								
	6.		oehind nozzleman far			hose to him/her.				
	7.	Removes l	kinks in hoseline duri	ng advancemen	ıt.					
	8.	Keeps hos	seline opposite protruc	ding corners to	avoi	d kinking.				
	9.	Advances	hoseline based on the	need of the no	zzle f	firefighter.				
	10.	Joins the r	nozzle firefighter after	r the hoseline is	in p	osition.				
	11.	Upon orde	er from nozzle firefigh	nter ventilates s	truc	ture.				
	12.	Assists wit	th overhaul of burning	g materials wit	h a t	ool, not the hands.				
	13.	Orders no	zzle firefighter back t	to origin to wet	buri	ning materials if				
		necessary.	•							
	14.	Assures fin	re is overhauled and e	extinguished.						
	15.	Completes	s evolution using safe	fire suppression	n ski	lls.				

Failure of this critical portion is cause	for entire skill failure	
Examiner Name	-	
Examiner Signature	_ Date/	

Sl	kill Sl	neet No.	FF-I- 813	07-01-07	Candidate Number				
Sl	kill Ti	itle: EX	KTINGUISH AN INTE	RIOR CLASS	S "A" MATERIALS	ABOV	V E		
		GR	RADE FIRE - SECONI	D BACKUP					
N	FPA	Objective:	5.3.10 & 5.3.13	N	Minimum to pass		9		
Pl	ERFC	RMANCE	E:				P		F
	1.		l protective clothing and ı	ıtilizes positive	pressure SCBA.				
	2.	Activates 1	PASS device.						
	3.	Takes a po	osition on the same side of	f the hoseline r	elative to nozzleman.				
	4.	Takes a fo	orcible entry tool.						
	5.	Stays low	when entering structure of	displaying host	ile/low visibility				
		conditions.							
	6.	Remains outside of doorways while advancing hoseline.							
	7.	Removes kinks in hoseline during advancement.							
	8.	Keeps hoseline opposite protruding corners to avoid kinking.							
	9.	Advances hoseline based on the need of the nozzle firefighter.							
	10.								
		advance m		-					
	11.	Moves up	to fire area if called by th	e nozzle, the fi	rst backup firefighter,	or			
		once extra hose is no longer needed.							
	12.	Overhauls	s burning materials when	ordered by no	zzle firefighter.				
	13.	Completes	s evolution using safe fire	suppression sk	ills.				
		-							

Failure of this critical portion is cause	e for entire skill failure	
Examiner Name	_	
Examiner Signature	Date/	

			1			
Ski	Skill Sheet No. FF-I- 814 07-01-07 Candidate Number					
Ski	11 7	Γitle: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS BEL	.OW			
		GRADE FIRE-NOZZLE FIREFIGHTER				
NF	PA	A Objective: 5.3.10 & 5.3.11 Minimum to pass	17			
		ORMANCE:	P	F		
1	l .	Wears full protective clothing and utilizes positive pressure SCBA.				
2	2.	Activates PASS device.				
	3.	Sets nozzle for a 30-degree fog pattern with a minimum flow of 95 GPM.				
4	l.	Slowly opens the nozzle fully, prior to entering the structure, to expel air and	_	_		
	_	test the fog pattern.				
5	5.	Feels door low to high, using the back of an ungloved or partially ungloved				
	_	hand, prior to opening.				
).	Assures that the other two firefighters are ready to enter the structure.				
_	7.	Opens door slowly and allows trapped heat and smoke to ventilate the area.				
8	_	Stays low when entering structure displaying hostile/low visibility conditions				
	9. Keeps hose line in the outer half of the stairway.					
1	10. With hose line and while staying low, descends stairwell as quickly as possible					
1	11	to get underneath thermal layer.				
1	1.	Keeps nozzle closed while advancing to fire unless necessary to operate for protection.				
1	12.	Upon reaching the fire, manages fire stream safely and properly based on the				
		conditions present.				
1	13.	Calls for first backup firefighter to open the structure for ventilation, if				
		possible.				
1	4.	Places nozzle outside of the building in preparation to ventilate hydraulically.				
1	15.	Slowly opens the nozzle.				
1	6.	Retracts the nozzle into the building approximately two (2) feet.				
1	7.	Adjusts fog pattern to fill approximately 85-90% of the opening with the				
		stream slightly touching the sides of the opening.				
		Holds stream steady until smoke has cleared or ordered back to the fire origin.				
1	9.	Stops hydraulic ventilation by advancing the nozzle outside the building				
		opening.				
	20.	Slowly closes the nozzle.				
	21. Assures fire is overhauled and extinguished.					
2	22. Completes evolution using safe fire suppression skills.					

Failure of this critical portion is cause f	or entire skill failure
Examiner Name	
Examiner Signature	Date/

Skill S	heet No. FF-I- 815	07-01-07	Candidate Number				
Skill T	itle: EXTINGUISH AN INTERIC	OR CLASS	"A" MATERIALS	BELC)W		
	GRADE FIRE-FIRST BACK	CUP					
NFPA	Objective: 5.3.10 & 5.3.11	M	Iinimum to pass		11		
	ORMANCE:	<u>'</u>	1		Р		F
1.	Wears full protective clothing and utiliz	zes positive j	pressure SCBA.				
2.	Activates PASS device.						
3.	Takes a position on the same side of the	e hoseline re	lative to nozzleman.				
4.	Carries a forcible entry tool.						
5.	Stays low when entering structure displ	laying hostil	e/low visibility				
	conditions						
6.	Keeps hose line in the outer half of the stairway.						
7.	Removes kinks in hose line during advancement.						
8.	Keeps hose line opposite protruding corners to avoid kinking.						
9.	Advances hose line based on the need of the nozzle firefighter as quickly as						
	possible to get underneath thermal laye						
10.	Joins the nozzle firefighter once the hos						
11.	Upon order from nozzle firefighter, ope	ens structure	e for ventilation, if				
	possible.						
12.	Overhauls burning materials with the to						
13.	Orders nozzle firefighter back to origin	to wet burn	ning materials, if				
	necessary.						
14.	Assures fire is overhauled and extinguis						
15.	Completes evolution using safe fire suppression skills.						

Failure of this critical portion is cause f	for entire skill failure	_
Examiner Name		
Examiner Signature	Date/	

Skill S	heet No.	FF-I- 816	07-01-07	Candidate Number				
Skill T	Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS BELOW							
	GF	RADE FIRE-SECOND B	BACKUP					
NFPA	Objective:	5.3.10 & 5.3.11	N	Minimum to pass		9		
PERFO	ORMANCI	E:				P		F
1.	Wears full	l protective clothing and uti	ilizes positive	pressure SCBA.				
2.	Activates	PASS device.						
3.	Takes a po	osition on the same side of t	the hoseline re	elative to nozzleman.				
4.	Carries a	forcible entry tool.						
5.	Stays low	when entering structure dis	splaying hosti	le/low visibility				
	conditions.							
6.	Keeps hose line in the outer half of the stairway.							
7.	Removes kinks in hose line during advancement.							
8.	8. Keeps hose line opposite protruding corners to avoid kinking.							
9.	Advances hose line based on the need of the first backup firefighter.							
10.	· · ·							
	advance more hose.							
11.	Moves up	to origin if called by the no	zzleman, first	backup firefighter, or as				
	the need for more hose ceases.							
12.	Assures that burning material is overhauled and fire is extinguished.							
13.	Completes	s evolution using safe fire su	uppression ski	ills.				

Failure of this critical portion is cause f	or entire skill failure
Examiner Name	
Examiner Signature	Date/